SPECTRA CYC UV 50W LED

The Spectra Cyc UV 50 is a 50 Watt cyclorama wall wash luminaire utilizing high output 365nm UV LED emitters.. Designed for theatrical and architectural applications, the Spectra Cyc UV 50 blends the output via a patented reflector providing smooth and even distribution.


Designed for use on 4-foot centers, individual units can be placed side by side for greater saturation of light. The Spectra Cyc UV 50 is compatible with both DMX and RDM protocols, and comes complete with a library of pre-programmed single colors to various color mixes. Units are made for floor, sky-cyc applications, or track mount applications.





Spectra Cyc UV 50

Product Features:

- Uses 365nm UV LEDs
- Asymmetrical reflector designed for broad, even distribution
- On-board multi-voltage power supply 100-240VAC.
- · Feed through power and data capabilities using
- PowerCON and 5-pin XLR connectors.
- · Compatible with DMX and RDM protocols
- · Push button addressing
- Preprogrammed modes for standalone intensity settings, timed intensity fades, and strobes
- Includes dual "kick stand" style yoke
- Weight: 7 lbs. / 3.2 kg (approximate)
- · Convection cooled, no fans
- · cETLus listed for indoor use and CE marked
- Made in the USA
- Five (5) year and one (1) day warranty
- No cost technical support for the life of your product











Specifications

Materials: Corrosion-resistant materials and hardware

Control: DMX (Fully RDM Compliant)

Light Engine 365nm UV LEDs
Power: 50 Watts
Voltage: 120-240VAC

Cooling: Passive, convection

Environment: 0 to 40 degrees C (32 to 104 degreesF) / 5%-

95% Non condensing

AC out: Flush mount PowerCON for feed thru power

to other Spectra Cyc units only.

Color: Black or White. Custom colors available -

consult factory before ordering.

Weight: 7lbs. (3.2kgs.)

Compliance: cETLus listed, CE marked
Warranty: Five (5) years and One (1) day

Support: Supported Forever - free phone and online

tech support for the life of your product.

NOTE:

A maximum recommended spacing is 4-foot on center, 2 to 4-foot back from lighted area. For a brighter, more saturated effect, Spectra Cyc UV 50 fixtures can be set closer together and to the lighted area.

Ordering Information

SSCYCUV50-(Body Color)

Model: SSCYCUV50 Spectra Cyc UV 50

Body Color: Black (B) or White (W) or Custom (C)**

SSCYCUV50Y-(Body Color)

Model: SSCYCUV50Y Spectra Cyc UV 50

Body Color: Black (B) or White (W) or Custom (C)**

Notes:

**Black (B) or White (W) or Custom (C). Consult factory for

custom

Optional Accessories

SC-36-BK Safety Cable

510 Malleable Iron Pipe C-ClampFT Black Floor Trunnion, Pair

SS-CYC50- Spectra Cyc 50 Yoke with Hardware for 1 Fixture

YOKE** (includes 510 C-clamp.)