VARI*LITE

VLZ SPOT



The ideal replacement solution to the VL3500 Series (profile) spot or any other 1,000W to 1,500W lamped professional moving profile light.

The Vari-Lite VLZ Spot is a dedicated spot luminaire utilizing the latest high output white LED sources to produce a staggering 25,000 lumens projected from a 180mm (7") front lens.

The Enhanced Fan control system allows users to choose one of 4 different fan levels to match the output they require for their show, remotely from their console. The familiar CMY-CTO color system creates stunning, seamless mixed colors. The dual fixed color wheel with linear control gives access to Vari-Lite colors and split color combinations. Color shake and color wheel spin control have also been added to the mix.

Dual rotating and indexable gobo wheels produce stunning mid-air and break up effects. The high contrast flat field wide zoom range and iris will cover beam control from the narrowest shafts of light to a hard focused wide projection. Multiple beam effects can be produced using the 3 faceted linear prism. Hard to soft edge focusing is attained via the 16-bit focus control channel, and focus zoom tracking can be selected remotely via a console. The beam softness can be adjusted via the 3 way frost control.

From concerts to opera, the combination of the color and beam control makes the VLZ Spot the go-to professional moving spot luminaire for mutiple large entertainment aplications.



VLZ SPOT

FEATURES & BENEFITS

- 25,000 lumen output.
- Wide zoom range 7-50° zoom.
- Large stage impact 180mm (7") front lens.
- Multiple fan level controls:

Standard


Studio

Studio 2

Whisper

- 16-bit dimmer control with 4 sectable curves.
- Camera friendly separate frequency and gamma control of LED array.
- Full color mixing and color effects CYM + CTO 2 color wheels total of 12 fixed color shake and wheel spin functions.
- Projection and mid-air effects:
 Gobo wheel 1 & 2: 7 interchangeable fully rotating and indexing gobos
 Gobo wheel 2: 7 interchangeable fixed gobos.
- Multi beam effects 3 facet prism.
- Beam edge softening 3-way frost control.
- Beam reduction ol variable Iris.
- Fast, accurate and repeatable movement on all functions.

VLZ SPOT FAN CONTROL MODES					
Mode	Output	Ambient	Fixture dB level	Distance	
Standard	100%	30	50.8 dB	1m / 3.3ft	
Studio	83%	30	41.0 dB	1m / 3.3ft	
Studio 2	67%	30	36.5 dB	1m / 3.3ft	
Whisper	58%	30	32.3 dB	1m / 3.3ft	






VLZ SPOT


SOURCE				
Туре		LED		
	Wattage	620W		
OPTICAL PERFORMANCE				
	Lumen output (max.)	25,000		
	Color temperature source	8000K		
Color temperature output		7000K		
	CRI / Ra	>70		
	Dimming system	Electronic 16-bit		
BEAM				
	Beam angle	7-50°		
IMAGING				
	Gobo 1	Glass interchangeable re	otation 7 + open	
	Gobo 2	Glass interchangeable rotation 7 + open		
	Gobo 3	Glass interchangeable fixed 8 + open		
	Prism	3 facet round		
	Frost	3 way frost system		
	Framing shutters / beam shaping	No		
	Iris	Yes		
COLOR				
	Color system	CMY, variable CTO 2 x fi	xed color wheels 6 + open	
MOVEME	NT			
	Pan / tilt	540° / 270°		
DATA PRO	OTOCOLS			
	Controls	DMX512-A / RDM, Art-Net™		
	DMX channels	42		
POWER				
	Operating voltage	100-240VAC, 50/60Hz		
ENVIRON	MENT	°C	°F	
	Operating temperature	-10-45°	14-113°	
PHYSICA	LS			
	IP rating	IP20		
	Finish	Black		
	Construction	Metal frame, engineering plastic covers		


VARI*LITE

VLZ SPOT

DIMENSIONS		mm	in
HxV	W x L	458 x 316 x 809	18 x 12.4 x 31.9
Hang	ging centers	682	27.875
WEIGHT		kg	lb
Weig	ght	44	97
WARRANTY & APPROBATION			
Warr	ranty	2 years	
Approvals / listings		CE, ETL, UL, FCC CSA, RoHS, ISO 9001	









VLZ SPOT	ORDER CODE
Vari-Lite VLZ automated LED Spot with input power powerCON connector AC100-240V	26-105-0001-00
Luminaire programing kit	PEGASUS

© 2018 Signify Holding. All rights reserved.

All trademarks are owned by Signify Holding or their respective owners. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Data subject to change.

Ref: 26-105-0001-00-SpecSheet-01